

Public Works (1897) Department.

G.O., No. 1317. W.

DATED 19 May 1897

Today

2/13/97

[Despatch Abstract.]

Madras Steam Boilers & Prime Movers' Act III of 1893. Ordered that a notification making ^{certain} rule under the —, be published in the Fort St. George Gazette

90/4

20/5/97

Index

20/5

BACK PAPERS.

FURTHER PAPERS.

GENERAL.
ESTABLISHMENT.

Government { 1897 } of Madras.
PUBLIC WORKS.

Recd.

Regd.

1897.

Enclosures

Spare copies

G.O., No. 1317 W., 19th May 1897.

MAY.

Madras Steam Boilers and Prime Movers Act III of 1893

Ordered that a notification making certain rule under the —, be published in the *Fort St. George Gazette*.

No. 1317 W., 19TH MAY 1897.

GOVERNMENT OF MADRAS.

PUBLIC WORKS DEPARTMENT.

General.
Establishment.

READ—again the following paper:—

G.O., No. 1018 W., dated 10th April 1897.

ORDER—No. 1317 W, dated 19th May 1897.

Ordered that the following notification be published in the *Fort St. George Gazette*:—

NOTIFICATION.

Adverting to the notification published at page 566 of the *Fort St. George Gazette* of the 4th May 1897, Part I, and in exercise of the powers conferred by section 23 of Act III of 1893 (The Madras Steam Boilers and Prime Movers Act), His Excellency the Governor in Council is pleased to make the following rule under the said Act. It will appear as a footnote to the second formula in rule 21 of the rules published in the *Fort St. George Gazette* of the 26th January 1897, and will come into force from date of publication.

"When furnaces are fitted with two Adamson rings, the following formula may be substituted:—

$$\frac{11,400 \times T}{D} = \text{working pressure in lb. per square inch.}$$

Where T is the thickness of the plate in inches.

D outside diameter of furnace in inches.

and when furnaces are fitted with a series of Adamson rings not more than 23" apart, the formula to be used will be—

$$\frac{1,000 \times (T - 2)}{D} = \text{working pressure in lb. on the square inch.}$$

Where T = thickness in sixteenths of an inch.

D = outside of diameter of furnace in inches."

(True Extract.)

Under Secretary to Government.

To the Superintendent, Government Press.
" Sanitary Engineer.
" Local and Municipal Department.

Exd. T. K. Narayana Aiyangar.

No. 1317 W of 19 May 1897

PUBLIC WORKS DEPARTMENT.

PROCEEDINGS OF THE MADRAS GOVERNMENT.

G.O. 1018 W. dated 10th April 1897.

again
READ the following

Ordered that the following notification be published in the *Fort St. George Gazette*.

Notification.

Adverting to the notification published at page 566 of the *Fort St. George Gazette* of the 4th May 1897, Part I, and in exercise of the powers conferred by Section 23 of Act III of 1893, The Madras Steam Boilers and Prime Movers Act, His Excellency the Governor in Council is pleased to make the following rule under the said Act. It will appear as a footnote to the second formula in rule 21 of the rules published in the *Fort St. George Gazette* of the 26th January 1897, and will come into force from date of publication.

"When furnaces are fitted with two Adamson rings, the following formula may be substituted—

$$\frac{11,400 \times T}{D} = \text{working pressure in lb. per square inch;}$$

Where T is the thickness of the plate in inches;

D outside diameter of furnace in inches;

and

and when furnaces are fitted with a
series of Adamson rings not more than
23" apart, the formula to be used will

be -
$$\frac{1,000 \times (T - 2)}{D} = \text{working pressure in lb. on the square inch;}$$

Where T = thickness in sixteenths of an inch;
D = outside of diameter of furnace in inches".

[Signature]
17/5/89

To

The Supt. Govt. Press.

,, Sanitary Engineer.

,, Local & Munl. Dept.

[Signature]
26/5/89